



You only get **one shot**
so make it count



Introducing Sachtler Ace

Sachtler is a worldwide market leader for professional camera support systems for cinematography and television production. Sachtler products symbolize top quality and reliability.

Now independent videographers can enjoy all the performance benefits of a broadcast quality offering – at a price that looks as good as the resulting image.

- Designed for low weight professional cameras
- Best-in-class drag performance
- Ergonomic and intuitive - designed for ease of use
- Best price to performance ratio in its class

Make it a winning shot with the Sachtler Ace.

Sachtler Ace M

Ace is ideally suited for small HDV camcorders and video-enabled DSLR cameras. With a payload range of 0 to 4 kilograms (0 to 8.8 lbs), a 5-step counterbalance and the new patented SA drag™, the new Ace tripod system enables a genuine Sachtler broadcast feel.

Due to its lightweight and compact design it is the perfect companion for work on the go whether you are working on low-budget documentaries, electronic news-gathering (ENG), weddings events and training videos or a secondary unit.

The new patented SA-drag™ system has three horizontal and three vertical steps. Ace uses three capsuled damping modules allowing you to choose a drag setting that suits any shooting situation - from a very tight control with lots of resistance to a very loose control with virtually no resistance at all. This technique gives, for the first time in this price segment, a constant and repeatable drag that professionals need and have always relied on, with Sachtlers' broadcast and cine heads.

The 5-step counterbalance capability ensures easy balancing and optimum positioning of the camera – a true Sachtler!

Technical and systems specification

Code	1001	1002
Name	System Ace M MS	System Ace M GS
Payload	0 - 4 kg / 0 – 8.8 lbs	0 - 4 kg / 0 – 8.8 lbs
Weight (without bag)	4.4 kg / 9.7 lbs	4.6 kg / 10.1 lbs
Bag	0.5 kg / 1.1 lbs	0.5 kg / 1.1 lbs
Height min.	78 cm / 30.7 in	57 cm / 22.4 in
Height max.	169 cm / 66.5 in	173 cm / 68.1 in
Transport length	85 cm / 33.5 in	87 cm / 34.3 in
Fluid Head Ace M		
Payload	0 - 4 kg / 0 – 8.8 lbs	
Weight (incl. pan bar, bowl clamp and camera plate)	1.7 kg / 3.7 lbs	
Counterbalance	5 steps + 0	
Drag	3 steps vertical and 3 horizontal, + 0	
Temperature range	-30°/+60°C -22°/+140°F	
Tilt range	+90 to -75°	
Camera plate	Ace plate (slide in)	
Camera screws	1/4", pin	
Spare screws	1/4", 3/8"	
Sliding range	104 mm / 4.1 in	
Camera platform	with scale	
Pan bar	1, fixed, Type Ace	
Leveling	level bubble	



Product features

- New patented SA-drag™ mechanism (Synchronised Actuated Drag)
- Long sliding range of camera plate
- Parking position for spare camera screws (1/4" and 3/8")
- Lightweight aluminium tripod
- Fiber glass reinforced composite fluid head
- Scale on camera platform