## 980

## iNetVu™

by C-COM Satellite Systems Inc.

## TECHNICAL SPECIFICATIONS





2 RG6 cables (10 m each)





0.98 m Circular Antenna

Elevation over Azimuth

**Flectrical** Rx & Tx cable **Control Cables:** 

Standard: 10m Ext. Cable Optional: upto 75m available 1 to 200 Watt (Ku band) \* Transmit (Tx) Power Transmit (Tx) Frequency 13.75 - 14.50 GHz (Ku Band) Receive (Rx) Frequency 10.95 – 12.75 GHz (Ku Band) Midband Gain (+.2dB)

> 39.8 dBi Tx 41.3 dBi

Sidelobe Envelope, Co-Pol (dBi)

100I / DØ < 20° 29 - 25 Log Ø dBi 20° < Ø < 26.3° - 3.5 dBi 26.3° < Ø < 48° 32 - 35 Log Ø dBi 48° < Ø - 10 dBi (averaged)

Cross-Polarization Within B.P.

- 30 dB Max. Any Angle off Axis - 25 dB Max.

Physical

Mounting Plate L: 49.5" (1257mm) W: 18" (457mm) Stowed Dish Ext. Dims (1549mm) L: 61" W: 39.5" (1003mm) H: 18.25" (463mm) Deployed Height 52" (1320 mm) Max. Reflector Assembly Weight 30 lbs (13.7 kg) **Base Weight** 113 lbs (51.3 kg) **Total Weight** 143 lbs (65 kg)

**Environmental Survival** 

Wind Deployed 100 mph (160 km/h) Wind Stowed 140 mph (225 km/h) -40°F to 150°F (-40°C to 65°C) **Temperature** 

Operational

45 mph (72 km/h) Wind **Temperature** -22°F to 130°F (-30°C to 55°C)

\* Depending on size and weight for feed arm mounting limitation

Mechanical Reflector Mount Geometry

Dish rotation cross-polarization Polarization isolation

**Deployment Sensors** GPS antenna Compass ± 2° Tilt sensor ± 0.2°

RF Interface Radio Mounting

Feed Arm / Rear of Base /Inside Vehicle **Axis Transition** Twist-Flex Waveguide Waveguide WR75 Cover Flange Interface Coaxial RG6U from Feedhorn to Base

Standard Feed Prodelin Model 1984 Based (2 Port - X Pol) European/Eutelsat Feed Prodelin Model 1985 Based (2 Port - X Pol)

**Electrical Interface** 12V DC 15A max.

**Maximum Mount Rotation** 

Azimuth Full 360° in overlapping 200°

sectors

Elevation 0 - 65° .±70° Polarization

**Elevation Deploy Speed** Variable 5°/sec typ Azimuth Deploy Speed Variable 15°/sec max,

10°/sec typ 0.2º/sec

Peaking Speed

Note:

Systems are configured with Cross-Pol as standard, Co-Pol is optional. A Eutelsat Feed is also available as an option for this system.

Standard warranty: 2 years

